



Flatpack2 24/2000

Rectifier Module

Versatile and powerful solution for any application

The combination of cost-effective design, power density and reliability makes the Flatpack2 a product family that truly stands out and provides unparalleled network availability. The versatility of the Flatpack2 rectifier means that it can be used in a wide variety of 48VDC and 24VDC applications across the globe.

Applications

Wireless, fiber and fixed line communication

Today's communications demand state of the art, cost effective and compact DC power systems. Flatpack2 delivers an industry leading power density and superb reliability at lowest lifetime cost

Broadband and network access

Increasing network speed demands flexible and expandable DC power solutions. The Flatpack2 rectifiers are your key building blocks for future needs.

Small and large

Due to the high power density, cost competitive design and a highly flexible system communication interface, Flatpack2 rectifiers are used in system solutions from 5kW to 96kW.

Product Description

The Flatpack2 is a battery charger and rectifier for stand-alone use or for working in parallel as part of a DC power system controlled and monitored by the Smartpack.

Flatpack2 is optimized for a wide range of system sizes. Digital communication over CAN bus with Smartpack simplifies system design and enhances flexibility.

Realization of Flatpack2 systems is possible by fitting 4 rectifiers across a 23" or 19" shelf.

Key Features

Highest efficiency in minimum space

Resonant topology makes the module efficiency industry leading and contributes to the rectifier's ultra compact dimensions.

Digital controllers

Primary and secondary controls are digitalized, enabling excellent monitoring and regulation characteristics. Thus, the number of component has been reduced by 40% - for highly reliable, long life, trouble free DC power systems.

Heat management

Front-to-back air flow with chassis-integrated heat sinks gives the module the most suitable working environment and no limitations in the scalability of the desired system solution.

Unique connection

A true plug-and-play connection system: time-to-install and cost-reducing solution.

Global approvals

Flatpack2 is CE marked, UL recognized and NEBS certified for world wide installation.

Flatpack2 24/2000

Additional Technical Specifications

AC Input	
Voltage	85-290 VAC (Nominal 176 – 275 VAC)
Frequency	44 to 66Hz
Maximum Current	13.0 A _{rms} maximum at nominal input and full load
Power Factor	> 0.99 at 50% load or more
Input Protection	<ul style="list-style-type: none"> Varistors for transient protection Mains fuse in both lines Disconnect above 290 VAC

DC Output	
Voltage	26.7 VDC (adj. range: 21.0-29.0 VDC)
Output Power	<ul style="list-style-type: none"> 2000 W at nominal input 1800 W at nominal input above 28.0 VDC
Maximum Current	84.0 Amps at 24 VDC and nominal input
Current Sharing	±5% of maximum current from 10% to 100% load
Static voltage regulation	±0.5% from 10% to 100% load
Dynamic voltage regulation	±5.0% for 10-90% or 90-10% load variation, regulation time < 50ms
Hold up time	> 20ms; output voltage > 21 VDC at 1000W load
Ripple and Noise	<ul style="list-style-type: none"> < 100 mV peak to peak, 30 MHz bandwidth < 0.96 mV rms psophometric
Output Protection	<ul style="list-style-type: none"> Overvoltage shutdown Blocking diode Short circuit proof High temperature protection

Other Specifications	
Efficiency	Typical 89%
Isolation	3.0 KVAC – input and output 1.5 KVAC – input earth 0.5 KVDC – output earth
Alarms:	<ul style="list-style-type: none"> Low mains shutdown High temperature shutdown Rectifier Failure Overvoltage shutdown on output Fan failure, one or two fans. Low voltage alarm at 21.0V CAN bus failure
Warnings:	<ul style="list-style-type: none"> Low temperature shutdown Rectifier in power derate mode Remote battery current limit activated Input voltage out of range, flashing at overvoltage Loss of CAN communication with control unit, stand alone mode
Visual indications	<ul style="list-style-type: none"> Green LED: ON, no faults Red LED: rectifier failure Yellow LED : rectifier warning
Operating temp	-40 to +75°C (-40 to +167°F)
Storage temp	-40 to +85°C (-40 to +185°F)
Cooling	2 fans (front to back airflow)
Fan Speed	Temperature and load regulated
MTBF	> 240,000 hours Telcordia SR-332 Issue I, method III (a) (T _{ambient} : 25°C)
Acoustic Noise	< 65dBA at nominal input and 70% load (T _{ambient} < 30°C)
Humidity	<ul style="list-style-type: none"> Operating: 5% to 95% RH non-condensing Storage: 0% to 99% RH non-condensing
Dimensions	109 x 41.5 x 327mm (wxhxd) (4.25 x 1.69 x 13")
Weight	1.9 kg (3.97 lbs)

Applicable Standards	
Electrical safety	IEC 60950-1 UL 60950-1 CSA 22.2
EMC	ETSI EN 300 386 V.1.3.2 (telecommunication network) EN 61000-6-4 (emission, industry) EN 61000-6-3 (emission, light industry) EN 61000-6-2 (immunity, industry) EN 61000-6-1 (immunity, light industry) Telcordia NEBS GR1089 CORE
Mains Harmonics	EN 61000-3-2
Environment	ETSI EN 300 019-2 ETSI EN 300 132-2 Telcordia NEBS GR63 CORE Zone 4 RoHS compliant

Specifications are subject to change without notice

241115.200.DS3 - v2

Ordering Information

Part no.	Description
241115.200	Flatpack2 24/2000